

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: **June 27, 2007**
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **Alkapam A Series**
Alkapam A-1103D
Alkapam A-1703
Alkapam A-1703D

PRODUCT USE: Drilling fluid additive.
CHEMICAL FAMILY: Anionic water soluble polymer CAS#: 25085-02-3

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not a controlled product under WHMIS.
WORKPLACE HAZARD: Treat as a nuisance dust.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
-------------------	----------------	-------------------	--------------------------------	---------------------------------	------------------

Contains no WHMIS controlled ingredients.

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [] EYE CONTACT [] SKIN [XX] INHALATION [] INGESTION
EYE CONTACT: May cause mechanical irritation.
SKIN CONTACT: Prolonged contact may cause slight irritation or dermatitis in some individuals.
INGESTION: No adverse effects expected. Product may swell in throat causing choking.
INHALATION: Dust may cause upper respiratory tract irritation.

**UNUSUAL FIRE AND
EXPLOSION HAZARDS:**

Will burn under fire conditions. If dusted this product may be an explosion hazard.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid contact with strong oxidizing agents. Avoid dusting conditions in presence of ignition sources.	
CONDITIONS OF REACTIVITY:		
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of nitrogen and oxides of carbon on combustion.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	Suggest NIOSH/MESA approved dust mask. Use approved respirator with dust cartridge if TLV is exceeded.
VENTILATION:	Use local exhaust, process enclosure or other engineering controls to maintain dust level below TLV.
PROTECTIVE GLOVES:	Suggest plastic or rubber.
EYE PROTECTION:	Safety glasses or goggles should be worn when handling this material.
OTHER PROTECTIVE EQUIPMENT (Specify):	Suggest rubber apron. Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid breathing dusts. Avoid direct or prolonged contact with skin and eyes. Use nonsparking tools and ground/bonded equipment and containers when transferring. Avoid creating dusts, as this product is pyrophoric in powder form. Any containers or equipment used should be decontaminated immediately after use. Store in a cool, dry area away from oxidizers and ignition sources.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Eliminate ignition sources. Sweep up and place in an appropriate closed container. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal. Clean up residual material by washing area with water.

WASTE DISPOSAL METHOD

Dispose/incinerate in accordance with federal, provincial and local regulations. **This product may be suitable for disposal by land fill; check with local operator.** It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: **June 27, 2007**

BY: Product safety committee

SUPERSEDES: **July 28, 2004**

PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**