

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: February 21, 2007
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **FlowStop**

PRODUCT USE: Oilwell drilling fluid additive
CHEMICAL FAMILY: Mixture CAS #: Mixture

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2A
WORKPLACE HAZARD: Potential carcinogen; contains free silica

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
Mica	5 – 10	12001-26-2	Not available	Not available	3 mg/m ³
Quartz; crystalline silica	0.1 – 1.0	14808-60-7	Not available	Not available	0.05 mg/m ³

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [] EYE CONTACT [] SKIN [XX] INHALATION [] INGESTION
EYE CONTACT: May cause mechanical irritation and/or damage.
SKIN CONTACT: May cause transient irritation.
INGESTION: May cause gastrointestinal irritation, nausea and diarrhea.

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not flammable
FLAMMABLE LIMITS:	Not applicable
EXTINGUISHING MEDIA:	Use media suitable for surrounding materials and packaging.
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid contact with strong oxidizers, strong acids and strong alkalies. Keep away from open flames.	
CONDITIONS OF REACTIVITY:	None known.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of carbon and other toxic vapours upon combustion.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	NIOSH approved dust masks or respirators for silica bearing dust.
VENTILATION:	Use local exhaust ventilation, process enclosure or other engineering controls to maintain PEL's/TLV's
PROTECTIVE GLOVES:	Personal preference.
EYE PROTECTION:	Safety glasses or goggles recommended.
OTHER PROTECTIVE EQUIPMENT (Specify):	Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid creating dust. Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact. Launder contaminated clothing before reuse. Store in cool, dry area. Empty packages contain residual hazardous material and should be handled as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Avoid breathing dust; wear an approved respirator. Vacuum up, if possible, to avoid generating airborne dust. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED:	February 21, 2007	BY:	Product safety committee
SUPERSEDES:	None	PHONE:	780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**