

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: **March 2, 2010**
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **OILGEL 3000**

PRODUCT USE: Oilwell drilling fluid additive
CHEMICAL FAMILY: Organophilic clay CAS #: Not available

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2A
WORKPLACE HAZARD: Long-term inhalation may cause cancer; may form flammable or explosive dust clouds

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
Quartz; crystalline silica	1-5	14808-60-7	Not available	Not available	0.025 mg/m³

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [] EYE CONTACT [] SKIN [XX] INHALATION [] INGESTION
EYE CONTACT: Mechanical irritant.
SKIN CONTACT: No effects expected.
INGESTION: Low oral toxicity. No effects expected.

INHALATION:	May cause irritation of the upper respiratory tract. This product contains crystalline silica. Breathing silica containing dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Chronic inhalation may cause silicosis, a progressive, disabling and sometimes fatal lung disease. Chronic inhalation exposure to crystalline silica quartz has been observed to cause lymph node effects, kidney effects and auto-immune disease.
CARCINOGENICITY:	This product is not listed by ACGIH, IARC, NTP or OSHA. Crystalline silica, when inhaled from occupational sources, is considered as a human carcinogen by IARC (Class 1) and by NTP. ACGIH classifies crystalline silica, quartz, as a suspected human carcinogen (A2).
TERATOGENICITY:	No information available. No adverse reproductive effects are anticipated.
REPRODUCTIVE TOXICITY:	No information available. No adverse reproductive effects are anticipated.
MUTAGENICITY:	Crystalline silica has been shown to cause mutagenic effects in human cells in-vitro.
SYNERGISTIC PRODUCTS:	None known.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT:	Wash with soap and water. If irritation persists, or develops, seek medical attention.
EYE CONTACT:	Flush with gently flowing warm water until particles are removed and irritation ceases. If irritation persists, contact a physician.
INGESTION:	If large amounts ingested, obtain medical attention.
INHALATION:	Move to area free from dust. If breathing difficulties continue, obtain medical attention. Inhalation may aggravate existing respiratory illness.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Pale grey to buff powder; no odour
SPECIFIC GRAVITY:	Not available
BOILING POINT (°C):	Not available
MELTING POINT (°C):	Not available
SOLUBILITY IN WATER:	Insoluble pH: Not available
PERCENT VOLATILE BY VOLUME:	Not applicable
EVAPORATION RATE:	Not applicable
VAPOUR PRESSURE (mmHg):	Not applicable
VAPOUR DENSITY (air = 1):	Not applicable
BULK DENSITY:	Not available

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Does not flash (organic dust).
FLAMMABLE LIMITS:	UEL: No upper limit LEL: 73.6 g/m ³
EXTINGUISHING MEDIA:	Use media suitable for surrounding materials and packaging.
SPECIAL FIRE FIGHTING PROCEDURES:	Control dust cloud formation. Self-contained breathing apparatus required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Normal precautions for organic dusts should be provided. Avoid dust concentrations above the lower explosive limit. Avoid dust contact with sources of ignition.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid ignition sources.	
CONDITIONS OF REACTIVITY:	None known.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Possible traces of carbon dioxide and ammonia.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	NIOSH approved dust masks or respirators for silica bearing dust.
VENTILATION:	Use local exhaust ventilation, process enclosure or other engineering controls to maintain PEL's/TLV's
PROTECTIVE GLOVES:	Personal preference.
EYE PROTECTION:	Safety glasses or goggles recommended.
OTHER PROTECTIVE EQUIPMENT (Specify):	Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid creating dust. Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact. Slippery when wet. Store in cool, dry area. Empty packages contain residual hazardous material and should be handled as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Avoid breathing dust; wear an approved respirator. Vacuum up, if possible, to avoid generating airborne dust. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal. Do not flush with water; becomes slippery when wet.

WASTE DISPOSAL METHOD

Dispose of in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. May be disposed of as an inert solid in a sanitary landfill in some locations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: **March 2, 2010** BY: Product safety committee
SUPERSEDES: **March 11, 2007** PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**