

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: **February 17, 2010**
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **POTASSIUM CHLORIDE (Potash)**

PRODUCT USE: Oilwell drilling fluid and cement additive.
CHEMICAL FAMILY: Inorganic salt CAS#: 7447-40-7

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not WHMIS controlled.
WORKPLACE HAZARD: Treat as nuisance dust.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
-------------------	----------------	-------------------	--------------------------------	---------------------------------	------------------

Contains no WHMIS controlled ingredients.

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: EYE CONTACT SKIN INHALATION INGESTION
EYE CONTACT: May cause mild irritation, including stinging, watering and redness.
SKIN CONTACT: May cause mild irritation including redness and a burning sensation.
Prolonged or repeated contact may cause dry skin. No information available on skin absorption.
INGESTION: Low to moderate degree of toxicity. LD₅₀ (oral-rat) = 2.6 g/kg.
Swallowing large amounts may cause irritation of the digestive tract including nausea, vomiting, diarrhea, abdominal cramping, irregular heartbeats, dehydration and hypertension.
INHALATION: High dust levels may cause upper respiratory tract irritation.
CARCINOGENICITY: No information available.

TERATOGENICITY: No information available.
REPRODUCTIVE TOXICITY: No information available.
MUTAGENICITY: No information available.
SYNERGISTIC PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Flush with water. Dry area thoroughly and apply skin cream or moisturizing cream. If irritation persists, obtain medical attention.
EYE CONTACT: Flush with gently flowing warm water for 15 minutes, or until irritation ceases. Hold eyelids open to ensure thorough flushing. If irritation persists, obtain medical attention.
INGESTION: Do not induce vomiting unless directed to do so by medical personnel. If large amount swallowed, obtain medical attention.
INHALATION: Move to fresh air. Apply oxygen or artificial respiration if required. If breathing difficulties, or distress, continue obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR: White to reddish-brown crystals; odourless
SPECIFIC GRAVITY: 1.986 – 1.990
BOILING POINT (°C): 1500 (sublimes)
MELTING POINT (°C): 773
SOLUBILITY IN WATER: 342 g/L @ 20°C pH: 8-9 (5% sol'n)
PERCENT VOLATILE BY VOLUME: 0
EVAPORATION RATE: Not applicable
VAPOUR PRESSURE (mmHg): ~0
VAPOUR DENSITY (air = 1): 2.57
BULK DENSITY: Loose; 1025 – 1200 kg/m³

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not flammable
FLAMMABLE LIMITS: Not applicable
EXTINGUISHING MEDIA: Use media suitable for surrounding materials and packaging.
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid contact with hot nitric acid; may cause evolution of toxic nitrosyl chloride. Contact with other strong acids may produce hydrogen chloride gas. May react violently with bromine trifluoride and may explode if mixed with potassium permanganate and sulfuric acid. Mildly corrosive to metals in the presence of moisture.	
CONDITIONS OF REACTIVITY:	Contact with incompatible materials.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Hydrogen chloride and fumes of Na ₂ O.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	Use NIOSH approved dust mask, or respirator with dust/mist filters, if TLV is exceeded. 8 hour OEL Nuisance Dust Total Mass = 10mg/m ³ .
VENTILATION:	Suggest local exhaust ventilation, if TLV's are exceeded.
PROTECTIVE GLOVES:	Suggest cloth or leather work gloves be worn to prevent skin contact.
EYE PROTECTION:	Safety glasses with side shields or goggles recommended.
OTHER PROTECTIVE EQUIPMENT (Specify):	Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Store in a cool, dry well-ventilated place away from incompatibles. Keep bags or fiber drums dry at all times. Product is hygroscopic (may absorb moisture from the air when relative humidity >72%).

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Potash is a crop nutrient and plant food, however large spills can harm or kill vegetation. Use appropriate safety equipment. Collect by sweeping and scoop up or shovel. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Keep out of sewers, storm drains, surface waters and soils. **Notify local, provincial and federal agencies as may be required.**

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. This product may be suitable for disposal in landfills; check with local operator. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Dispose of all packaging in accordance with local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: February 17, 2010

BY: Product safety committee

SUPERSEDES: February 15, 2007

PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**